## Ullens



As a manufacturer of state-of-the-art packaging machines Willems Stretch Hooding BV offers an innovative, high quality and efficient solutions for your packaging on pallets.



hooder

## Technical specifications:

Pallet dimensions:

Load dimensions: Pallet positioning: Maximum load: Capacity:

Transport height Power supply: Diameter filmreel: min. 800 x 600mm max. 1.600 x 1.200mm 1.750 x 1.350mm ±10mm 1.500Kg till 80 pallets per hour (depending on project specifications) 500mm-600mm (standard 600mm) 3x400V, 50Hz + Earth + "0" max. 1.000mm Load height: (incl. pallet) Load tolerance:

Transport speed: Installed power: min. 400mm max. 3.500mm offset max. 75mm

12mtr/min. 14 KW

<image>

Willems stretchhooder offers full protection against dirt, dust and moisture. The quality stretch hood film also protects your products against scratches and surface damage. Furthermore, the packaging machines deliver watertight hoods, in order to protect the value of your products.

Almost no maintenance required, the lifting and lowering of the stretch unit happens with toothed belts



We guarantee the best possible protection for your pallets with our high quality stretchhood machine





The Hooder L stretchhood offers a cost-effective solution for a broad range of pallet packages





Nijverheidstraat 7 • 5531 AA • Bladel • The Netherlands T: +31 (0) 497.64 58 62 E: info@stretchhooder.eu W: www.stretchhooder.com